






Advance warning lamps

Picture	Description	Order No.	Price € + VAT	
 <p>TL-tested!</p> <p>New: also with LED!</p>	<p>1 Advance warning lamp 340 mm Ø (12 volt/24 volt) BASSt test No.: V4-38-2001</p> <p>BASSt-tested according to TL Warning Lights type WL 7, with reverse polarity protection and undervoltage protection. For 12 or 24 V input voltage. The 12 V/35W halogen lamp is mounted in a splash-proof case and has a night-time reduction feature. Supplied with 3 m connection lead and fixture for 40x40 mm square tube. <i>Power consumption (12V): 1.6 A day / 0.8 A night; (24V): 0.8 A day / 0.4 A night</i></p> <p>Design as above but with LED technology. <i>Power consumption (12V): 0.3 A day / 0.2 A night; (24V): 0.15 A day / 0.1 A night</i></p> <p>Design as above but for use with 230 Volt / 60 W</p>	<p>W 5305</p> <p>W 5305L</p> <p>W 5304</p>	<p>203,--</p> <p>360,--</p> <p>199,--</p>	
	 <p>TL-tested!</p>	<p>2 Advance warning lamp 340 mm Ø (12 volt/24 volt) BASSt test No.: V4-39-2001</p> <p>BASSt tested according to TL warning lights type WL 5, with reverse polarity protection and undervoltage protection. For 12 or 24V input voltage. The electronic flashing light is mounted in a splash-proof case. Supplied with 3 m connection lead and fixture for 40x40 mm square tube. <i>Power consumption (12V): 0.2 A day / 0.1 A night; (24V): 0.12 A day / 0.05 A night</i></p>	<p>W 5306</p>	<p>230,--</p>
	 <p>NEW: also with LED!</p>	<p>3 Advance warning lamp 180 mm Ø (12 volt/24 volt)</p> <p>with reverse polarity protection and undervoltage protection. For 12 or 24 V input voltage. The 12 V/20W halogen lamp is mounted in a splash-proof case and has a night-time reduction feature. Supplied with 3 m connection lead and fixture for 40x40 mm square tube. <i>Power consumption (12V): 0.9 A day / 0.5 A night; (24V): 0.49 A day / 0.26 A night</i></p> <p>Design as above but with LED technology <i>Power consumption (12V): 0.1 A; (24V): 0.085 A</i></p>	<p>W 5301</p> <p>W 5301L</p>	<p>125,--</p> <p>189,--</p>
	<p>4 Advance warning flash 180 mm Ø (12 volt/24 volt)</p> <p>with reverse polarity protection and undervoltage protection. For 12 or 24V input voltage. The electronic flash light is mounted in a splash-proof case. Supplied with 3 m connection lead and fixture for 40x40 mm square tube. <i>Power consumption (12V): 0.110 A; (24V): 0.065 A</i></p>	<p>W 5302</p>	<p>149,--</p>	
 <p>TL-tested!</p> <p>NEW: also with LED!</p>	<p>5 Mobile advance warning lamp 340 mm Ø (12 volt/24 volt) BASSt test No.: V4-38-2001</p> <p>The TL-tested 340 mm Ø halogen warning lamp 12 V/35 W (with night-time reduction feature) is fitted to an adjustable pole on an aluminium battery casing for 1 battery 12 V/170 Ah. <i>Power consumption (12V): 1.6 A day / 0.8 A night; (24V): 0.8 A day / 0.4 A night</i></p> <p>Design as above but with 12V LED technology <i>Power consumption (12V): 0.3 A day / 0.2 A night; (24V): 0.15 A day / 0.1 A night</i></p> <p>Weight approx. 27 kg; supplied without battery.</p>	<p>W 4904</p> <p>W 4904L</p>	<p>520,--</p> <p>685,--</p>	